

potential response requirements outstanding and due in the above captioned matter.

Please amend the application as follows:

IN THE CLAIMS:

MARKED UP VERSION OF THE AMENDED CLAIMS

(Version with marking to show changes made)

1) (previously presented) In a chain drive having a rotatable chain wheel with pockets or teeth connected by straight lines to form a polygon for driving pivot chains or round link chains, the axis of said chain wheel rotatably fixed to a driven gear wheel of a spur gear driving arrangement, said driven gear wheel having a variably sized pitch circle for reducing variations in velocity and acceleration of said chain wheel, the improvement comprising: said spur gear driving arrangement including a driving gear wheel for driving said driven gear wheel at an adjusted gear ratio, said chain wheel and said drive gear rotatable on a common axis; and

at least one of said driving and driven gear wheels having a noncircular toothed gear wheel configuration established relative to the pitch circle and including a plurality of rolling curve means for causing said chain wheel to have a minimum angular velocity at a corner of said polygon and a maximum velocity at a mid-point of a straight side of said polygon while said driving wheel rotates at a constant angular velocity.

W/Cont
2) (original) The improvement of claim 1 wherein said polygon for said round link chains comprises a plurality of short straight lines and a plurality of long straight lines with a long straight line adjacent an end of a short straight line, said short straight lines corresponding to corners of said polygon, and the pitch circle radius of said noncircular gear wheel at the middle of any short straight line is greater than the pitch circle radius at the middle of any long straight line.

3) (withdrawn) The improvement of claim 1 wherein said chain drive has pivot chains, said driven gear wheel having said noncircular toothed

gear wheel configuration, said plurality of rolling curve means including a plurality of continuous rolling curve sections at the pitch curve circumference of said driven gear, said plurality of continuous rolling curve sections equal in number to the number of teeth in said chain wheel.

4) (previously presented) In a chain drive having a rotatable chain wheel with pockets or teeth connected by straight lines to form a polygon for driving pivot chains or round link chains, the axis of said chain wheel rotatably fixed to a driven gear wheel of a spur gear driving arrangement, said driven gear wheel having a variably sized pitch circle for reducing variations in velocity and acceleration of said chain wheel, the improvement comprising: said spur gear driving arrangement including a driving gear wheel for driving said driven gear wheel at an adjusted gear ratio, said chain wheel and said drive gear rotatable on a common axis; and at least one of said driving and driven gear wheels having a noncircular toothed gear wheel configuration established relative to the pitch circle and including a plurality of rolling curve means for causing said chain wheel to

have a minimum angular velocity at a corner of said polygon and a maximum velocity at a mid-point of a straight side of said polygon while said driving wheel rotates at a constant angular velocity,

wherein said polygon for said round link chains comprises a plurality of short straight lines and a plurality of long straight lines with a long straight line adjacent an end of a short straight line, said short straight lines corresponding to corners of said polygon, and the pitch circle radius of said noncircular gear wheel at the middle of any short straight line is greater than the pitch circle radius at the middle of any long straight line,

wherein said chain drive has round link chains, said driven gearwheel having said noncircular toothed gearwheel configuration, said rolling curve means including a plurality of continuous rolling curve sections at the pitch curve circumference of said driven gear, said plurality of continuous rolling curve sections equal in number to twice the number of teeth in said chain wheel.

5) (withdrawn) The improvement of claim 3 wherein said driving

gear wheel has a noncircular toothed gear wheel configuration, said noncircular configuration including a plurality of continuous rolling curve sections at the pitch curve circumference of said driving gear.

6) (original) The improvement of claim 4 wherein said driving gear wheel has a noncircular toothed gear wheel configuration, said noncircular configuration including a plurality of continuous rolling curve sections at the pitch curve circumference of said driving gear.

7) (withdrawn) The improvement of claim 5 wherein said driving gear wheel has an arbitrary number of said continuous rolling curve sections equal to or greater than one.

8) (original) The improvement of claim 6 wherein said driving gear wheel has an even number of said continuous rolling curve sections.

9) (original) The improvement of claim 1 wherein both said driven

and driving gear wheels have a noncircular toothed gear wheel configuration, said rolling curve means comprising a plurality of continuous rolling curve sections and the number of said continuous rolling curve sections for said driving gear wheel is set relative to a pitch angle of said driving gear wheel to establish a set gear ratio of said driving gear wheel to said driven gear wheel.

10) (withdrawn) The improvement of claim 9 wherein the geometric shape of said continuous rolling curve sections is set to produce a constant driving angular velocity determined by multiplying the driven angular velocity of said driven gear wheel determined by the expression $\omega_2 = \omega_1 / i$ with a gear ratio, i_m , established at the corner middle of said polygon and the cosine of the driven angle φ_2 , to achieve said set gear reduction, i , according to the relation $i = i_m \cos \varphi_2$ where:

ω_2 is the angular velocity of said driven gear wheel,

ω_1 is the angular velocity of said driving gear wheel,

φ_2 is the angle of rotation of said driven gear wheel.

11) (withdrawn) The improvement of claim 10 wherein said continuous rolling curve sections have a geometric shape that allows said set gear ratio, i , to be approximated by mathematical techniques selected from the group consisting of basic polynomials, composite polynomials, trigonometric functions, Fourier series, periodic mathematical functions, approximating mathematical functions, and sections of eccentric circular arcs.

12) (withdrawn) The improvement of claim 5 wherein a set gear ratio is established according to the relationship $i_m = \varphi_1 / \sin \alpha_2$

where:

i_m is the gear ratio at the corner middle of said polygon;

φ_1 is the angle of rotation of said driving gear wheel; and,

α_2 is the pitch angle of said driven gear wheel.

13) (original) The improvement of claim 6 wherein a set gear ratio is

established according to the relationship

$$i_m = \frac{\beta_1 + \gamma_1}{\sin \beta_2 + \sin \gamma_2}$$

where:

i_m is the gear ratio at the center of a short straight line of said polygon;

β_1 is the pitch angle of said driving gear wheel for said long polygon side;

β_2 is the pitch angle of said driven gear wheel for said long polygon side;

γ_1 is the pitch angle of said driving gear wheel for said short polygon side; and,

γ_2 is the pitch angle of said driven gear wheel for said short polygon side.

14) (original) The improvement of claim 1 wherein both said driven

and driving gear wheels have a noncircular toothed gear wheel configuration comprising a plurality of continuous rolling curve sections and the intersection of adjacent rolling curve sections of said driven gear wheel have concave, unilaterally bent adjustment curve surfaces tangential to said rolling curve sections.

15) (original) The improvement of claim 1 wherein both said driven and driving gear wheels have a noncircular toothed gear wheel configuration comprising a plurality of continuous rolling curve sections and the intersection of adjacent rolling curve sections of said driven gear is defined by an undulating adjustment curve surface in tangential contact at its ends to said rolling curve sections.

16) (original) The improvement of claim 15 wherein said undulating curve is mathematically defined as being selected from the mathematical group consisting of a polynomial of fourth order and a modified trigonometric function of $x \sin x$.

17) (original) The improvement of claim 14 wherein the radius of said undulating adjustment curve surface is equal to or greater than a radius of a cylindrical forming tool used to form said adjustment curve surface.

18) (withdrawn) The improvement of claim 1 wherein both said driven and driving gear wheels have a noncircular toothed gear wheel configuration comprising a plurality of continuous rolling concave curve sections and said driven gear wheel comprises first and second part components nested into one another in an assembled condition, each part component having pie sections separated by an arcuate gap and each pie section having at its outer edge a continuous rolling section whereby said pie section of one part component nests into said arcuate gap of the other part component to form said driven gear wheel.

19) (withdrawn) The improvement of claim 17 wherein said pie section for each part component extends radially inward to a centering hub section

recessed relative to an end face of a part component, said hub section of one part component in face contact with said hub section of the other part component to form said assembled driven gear wheel.

20) (original) The improvement of any one of claims 14 or 15 wherein the shape of said rolling curve sections adjacent the intersection of rolling curve sections is varied over a portion of each rolling curve section adjacent said intersection to maintain said set gear ratio.

21) (original) The improvement of any one of claims 3, 4, 9, 14 or 15 wherein said chain drive has a plurality of cascading driven and driving gear wheels so that the driven gear wheel of one driven and driving gear wheel set functions as the driving gear wheel ^{for} of another driven and driving gear wheel set.

22) (withdrawn) The improvement of claim 21 wherein at least one of said driven and driving gear sets that does not have its driven gear

rotatively fixed to said chain wheel is a circular gear set.

23) (withdrawn) The improvement of claim 21 wherein a plurality of driving and driven gear sets have noncircular rolling sections.

24) (original) A spur gear chain drive arrangement for driving pivot chains or round link chains comprising:


- W 24
- a) a chain wheel having pockets or teeth for driving said chains forming a straight sided polygon having corners at said teeth and long straight sides between adjacent teeth when said chains are pivot chains and straight short side corners at said teeth and long side straight sides between adjacent teeth when said chains are round link chains;
 - b) a driving spur gear connected to a source of rotation;
 - c) a driven spur gear rotatably fixed and circumferentially positioned relative to said chain wheel on a common axis of rotation and rotatably driven by said driving gear;

d) said driving and driven gears having teeth formed on a plurality of concave, noncircular rolling sections extending about each gear's pitch circle circumference, each noncircular rolling section having a distance from the center of each gear which is longest at the center of said corners of said polygon and shortest at the center of said long straight sides of said polygon and said distances and the number of said rolling sections being set to produce a desired gear ratio between said driving and driven gears whereby for constant rotation of said driving gear, angular velocities of said chain wheel varies as said driven gear rotates through a noncircular rolling section while velocities of said chains remain generally constant.

25) (withdrawn) The chain drive arrangement of claim 24 wherein said chain drive has pivot chains and said plurality of continuous rolling curve sections in said driven gear being equal in number to the number of

teeth in said chain wheel.

26) (previously presented) A spur gear chain drive arrangement for driving pivot chains or round link chains comprising:

- 
- e) a chain wheel having pockets or teeth for driving said chains forming a straight sided polygon having corners at said teeth and long straight sides between adjacent teeth when said chains are pivot chains and straight short side corners at said teeth and long side straight sides between adjacent teeth when said chains are round link chains;
 - f) a driving spur gear connected to a source of rotation;
 - g) a driven spur gear rotatably fixed and circumferentially positioned relative to said chain wheel on a common axis of rotation and rotatably driven by said driving gear;
 - h) said driving and driven gears having teeth formed on a plurality of concave, noncircular rolling sections extending about each gear's pitch circle circumference, each

noncircular rolling section having a distance from the center of each gear which is longest at the center of said corners of said polygon and shortest at the center of said long straight sides of said polygon and said distances and the number of said rolling sections being set to produce a desired gear ratio between said driving and driven gears whereby for constant rotation of said driving gear, angular velocities of said chain wheel varies as said driven gear rotates through a noncircular rolling section while velocities of said chains remain generally constant,

wherein said chain drive has round chains and said plurality of continuous rolling curve sections of said driven gear are equal in number to twice the number of teeth in said chain wheel.

27) (original) The chain drive arrangement of claims 25 or 26 wherein said driving gear has an arbitrary number of said continuous rolling curve sections equal to or greater than one.

28) (original) The chain drive arrangement of claim 27 wherein for round link chains said driving gear wheel has an even number of said continuous rolling curve sections.

29) (original) The chain drive arrangement of claim 27 wherein the number of said continuous rolling curve sections for said driving gear wheel is set relative to a pitch angle of said driving gear wheel to establish a set gear ratio of said driving gear wheel to said driven gear wheel.

30) (withdrawn) The chain drive arrangement of claim 27 wherein for pivot chains, a set gear ratio is established according to the relationship

$$i_m = \varphi_1 / \sin \alpha_2$$

where:

i_m is the gear ratio at the corner center of said polygon;

φ_1 is the angle of rotation of said driving gear wheel, and,

α_2 is the pitch angle of said driven gear wheel.

31) (original) The chain drive arrangement of claim 27 wherein for round link chains, a set gear ratio is established according to the relationship

$$i_m = \frac{\beta_1 + \gamma_1}{\sin \beta_2 + \sin \gamma_2}$$

where:

i_m is the gear ratio at the corner centers of said polygon;

β_1 is the pitch angle of said driving gear wheel for said long polygon side;

β_2 is the pitch angle of said driven gear wheel for said long polygon side;

γ_1 is the pitch angle of said driving gear wheel for said short polygon side; and,

γ_2 is the pitch angle of said driven gear wheel for said short polygon side.

32) (original) The chain drive arrangement of claim 27 wherein the intersection of adjacent rolling curve sections of said driven gear wheel have concave, unilaterally bent adjustment curve surfaces tangential to said rolling curve sections.

33) (original) The chain drive arrangement of claim 27 wherein the intersection of adjacent rolling curve sections of said driven gear is defined by an undulating adjustment curve surface in tangential contact at its ends to said rolling curve sections.

34) (withdrawn) The chain drive arrangement of claim 27 wherein said driven gear comprises first and second part components nested into one another in an assembled condition, each part component having pie sections separated by an arcuate gap and each pie section having at its outer edge a continuous rolling section whereby said pie section of one part component nests into said arcuate gap of the other part component to form said driven gear.

35) (withdrawn) The chain drive arrangement of claim 34 wherein said pie section for each part component extends radially inward to a centering hub section recessed relative to an end face of a part component, said hub section of one part component in face contact with said hub section of the other part component to form said assembled driven gear wheel.

36) (original) The chain drive arrangement of claim 27 wherein the configuration of said rolling curve section is in the shape of a cardioid and comprises that portion of a cardioid which most closely resembles a circular arc.

37) (original) The chain drive arrangement of claim 36 wherein said rolling curve section of said driving gear is determined by the mathematical function of

a

$$r_1(\varphi_1) = \frac{a}{\sqrt{i_m^2 - \varphi_1^2 + 1}}$$

where:

r_1 is locus of points defining the cardioid for the driving gear;

a is distance between driving and driven gear centers;

i_m is gear ratio at the middle of polygon corner;

φ_1 is angle of rolling curve arc of driving gear.

38) (withdrawn) The chain drive of claim 36 wherein said rolling curve section of said driven gear is determined by the mathematical expression:

$$r_2 = \frac{a \cdot i_m \cos \varphi_2}{1 + i_m \cos \varphi_2}$$

where:

r_2 is locus of points defining the cardioid for the driven gear;

a is the distance between centers of driving and driven gear;

i_m is the gear ratio at the middle of a polygon corner; and,

φ_2 is the angle of rolling curve arc of driven gear.

39) (previously presented) The chain drive according to claim 1 wherein the polygon is formed to drive a round link chain.

40) (previously presented) The chain drive according to claim 1 wherein the claim wheel polygon (29) is shifted outwardly by equipment polygon straight lines (26) for shifting together points of intersection (17) along the periphery.

41) (previously presented) The chain drive according to claim 1 wherein the chain wheel polygon (29) is shifted outwardly by equivalent polygon straight lines (26) for placing ten points of intersection (17) along the periphery.

42) (new) The chain drive arrangement of claim 24 wherein the driven chain is a round link chain (8), wherein a pitch curve radius (13a) of the driven spur gear wheel (3) is greater in a middle of a shorter equivalent polygon straight line (30) than in a middle of a longer equivalent polygon straight line (31).

43) (new) A chain drive comprising a driving gear wheel; a driven gear wheel engaged by the driving gear wheel, wherein the driving gear wheel and the driven gear wheel form a spur gear driving arrangement, wherein said spur gear driving arrangement is including the driving gear wheel for driving said driven gear wheel at an adjusted gear ratio; a rotatable chain wheel having peripheral engagement elements forming corner points connected by straight lines to form a polygon for driving chains, the axis of said chain wheel rotatably fixed to the driven gear wheel, wherein said chain wheel and said driven gear wheel are rotatable

on a common axis; wherein said driven gear wheel has a variably sized pitch circle for reducing variations in velocity and acceleration of said chain wheel;

wherein at least one of said driving gear wheel and said driven gear wheel has a noncircular toothed gear wheel configuration established relative to the pitch circle and including a plurality of rolling curve means for causing said chain wheel to have a first extremum of the angular velocity of the chain wheel at a corner of said polygon and a second extremum of the angular velocity of the chain wheel at a mid-point of a straight side of said polygon while said driving wheel rotates at a constant angular velocity.

44) (new) A spur gear chain drive arrangement for driving chains comprising:

a chain wheel having engagement elements for driving said chains, wherein the engagement elements form a straight sided polygon having corners at said engagement elements and long straight sides between adjacent engagement elements;

5143
a driving spur gear connected to a source of rotation;
a driven spur gear rotatably fixed and circumferentially positioned relative to said chain wheel on a common axis of rotation and rotatably driven by said driving spur gear;
wherein said driving spur gears and said driven spur gears include teeth formed on a plurality of concave, noncircular rolling sections extending about each spur gear's pitch circle circumference, wherein each noncircular rolling section has a distance from a center of each spur gear, which distance is longest at the center of said corners of said polygon and which distance is shortest at the center of said long straight sides of said polygon and said distances and the number of said rolling sections being set to produce a desired gear ratio between said driving and driven gears whereby for constant rotation of said driving gear, angular velocities of said chain wheel varies as said driven gear rotates through a noncircular rolling section while velocities of said chains remain generally constant.
